



StoPox WG 100

Sustainability

Data for building certification systems

Deutsche Gesellschaft für Nachhaltiges Bauen e.V. (German Sustainable Building Council, DGNB for short)		
ENV1.2, Version 2018	Product group:	No. 23: EP products for coating mineral surfaces on floors, ceilings, and walls – including in system buildups without special requirements
	Quality level:	Meets quality level 4 – GISCODE RE05, RE10, RE20, RE30, or RE90 and substantiation of emissions in accordance with MVV TB as an individual product or part of a system
ENV1.2, Version 2023	Product group:	No. 23: EP products for coating mineral surfaces on floors, ceilings, and walls – including in system buildups without special requirements
	Quality level:	Meets quality level 4 – GISCODE RE05, RE10, RE20, RE30, or RE90 and substantiation of emissions in accordance with MVV TB as an individual product or part of a system

Qualitätssiegel Nachhaltiges Gebäude (German Quality Label for Sustainable Building, QNG for short)		
Annex document 313 dated 14 September 2023	Product group:	No. 5.8: Synthetic resin screeds and reactive epoxy resin coatings (EP) on mineral floor and wall surfaces (interior and exterior) – including in system buildups
	Quality level:	Met – Synthetic resin screeds incl. synthetic resin coatings on floorings and wall coatings (interior): compliant with Committee for Health-related Evaluation of Building Products scheme (AgBB Germany) and GISCODE RE05, RE10, RE20, RE30, RE40, or RE50
Proposal for assignment: LCA calculation values for QNG Sustainable Building Certification	6.3 Synthetic resin screed	

Bewertungssystem Nachhaltiges Bauen (German Assessment System for Sustainable Building, BNB for short)		
BNB_BN 1.1.6, Version 2015	Product group:	No. 19: Epoxy resin coatings – including in system buildups for single-component and two-component systems
	Quality level:	Meets quality level 5 – Compliant with Committee for Health-related Evaluation of Building Products scheme (AgBB Germany) and TVOC ≤ 250 µg/m ³ after 28 days, and GISCODE RE1, RE0

Minergie-ECO / ecobau

Ecobau classification	Swiss environment label:	C
	Report number:	ECO-CH-028
	Ecobau:	Eco2
	Ecobau:	(Ecobau methodology for construction materials 2025/V01)
	Ecobau:	
	Report number:	

Leadership in Energy and Environmental Design (LEED v. 4.1)

VOC content (EQ Credit: Low-emitting materials)	19.9 g/l (Without water) calculated according to the SCAQMD METHOD 304-91 (5.1) Met in accordance with LEED v4	
VOC emissions (EQ Credit: Low-emitting materials)	Limit value:	In accordance with the Committee for Health-related Evaluation of Building Products (AgBB Germany)
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
SVOC emissions (EQ Credit: Low-emitting materials)	Limit value:	In accordance with the Committee for Health-related Evaluation of Building Products (AgBB Germany)
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
Formaldehyde emissions (EQ Credit: Low-emitting materials)	Limit value:	≤ 0.01 mg/m ³

Leadership in Energy and Environmental Design (LEED v. 4.1)

	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
Recycling percentage (post-consumer recycled content) (MR Credit: Sourcing of raw materials)	0 %	
Recycling percentage (pre-consumer recycled content) (MR Credit: Sourcing of raw materials)	0 %	
Renewable raw materials (bio-based materials) (MR Credit: Sourcing of raw materials)	0 %	

Building Research Establishment Environmental Assessment Method (BREEAM)

VOC content (EQ Credit: Low-emitting materials)	19.9 g/l (Without water) calculated according to the SCAQMD METHOD 304-91 (5.1) Met in accordance with BREEAM	
VOC emissions (Hea 02: indoor air quality)	Limit value:	≤ 0.3 mg/m ³
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
SVOC emissions (Hea 02: indoor air quality)	Limit value:	

Building Research Establishment Environmental Assessment Method (BREEAM)

	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
Formaldehyde emissions (Hea 02: indoor air quality)	Limit value:	
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
CMR emissions (Hea 02: indoor air quality)	Limit value:	$\leq 0.001 \text{ mg/m}^3$
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2

EU Taxonomy Regulation (EU) 2020/852

Compliant with Annex C	Met	
Note	This statement is based on the formulation data of Sto SE & Co. KGaA and information from our upstream suppliers.	
Formaldehyde emissions	Limit value:	
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2

EU Taxonomy Regulation (EU) 2020/852

Other carcinogenic VOCs in categories 1A and 1B (CMR)	Limit value:	≤ 0.001 mg/m ³
	Degree to which requirements are met:	Met
	Test institute:	TÜV Proficert PREMIUM
	Report type:	System test report
	Report number:	70 710 5715-2
Compliant with minimum social requirements (human rights, German Supply Chain Due Diligence Act, etc.)	https://www.stocretec.de/s/unternehmen/compliance	

Eco-labels and environmental labels

Eco-label, certificates

ISO certification 9001, 14001, 50001	https://www.stocretec.de/s/unternehmen/managementsysteme	
Environmental Product Declaration (EPD)	EPD-DBC20220174-IBF1-EN	
Product-specific working life (in accordance with BNB service life table)	Years:	40 years
	Application range:	Interiors
	Years:	20 years
	Application range:	exterior
Product-specific working life (in accordance with EPD)	Years:	> 50 years
	Application range:	Interiors
	Years:	> 50 years
	Application range:	exterior
GISCODE	See SDS (section 15)	

Product ingredients

Organic component (in accordance with natureplus / baubook)	>5%	
Hazardous substances (in accordance with EU regulations)	See SDS (section 3)	
CMR substances (VOC)	Present (in accordance with DIN EN ISO 17895)	
VOC content (in accordance with Directive 2004/42/CE)	1,34 g/l	
Solvent (in accordance with VdL Directive 01)	Content:	< 700 mg/kg Solvent-free
	Base:	According to formulation evaluation
Plasticiser (in accordance with VdL Directive 01)	Content:	< 500 mg/kg Plasticiser-free
	Base:	According to formulation evaluation
Free formaldehyde (in accordance with VdL Directive 01)	Content:	< 2 mg/kg Formaldehyde-free
	Base:	According to formulation evaluation
Biocide(s), active substance(s) for protection of the coating (in accordance with Regulation (EU) No 528/2012)	Not present	
Biocide(s), active substance(s) for protection of the product during storage (in accordance with Regulation (EU) No 528/2012)	Not present	
Heavy metals	Not assessed	
Compliant with the emissions restrictions of the titanium dioxide industry (in accordance with Directive 2010/75/EU and 25th Ordinance for the Implementation of the Federal Immission Control Act)	Yes	

SVHC in accordance with the REACH chemicals regulation (EC/1907/2006), Annex XIV	Content:	<0,1%
	Base:	According to formulation evaluation

Carbon footprint

A1-A3 (cradle to gate – manufacturing)	3.8 kg CO ₂ e / kg
A4 (transport from manufacturer to site)	0.054 kg CO ₂ e / kg
A1-C4 (cradle to grave – life cycle)	4.628 kg CO ₂ e / kg
D (Benefits and loads beyond the system boundary)	-0.373 kg CO ₂ e / kg
A1-D (cradle to cradle – life cycle including benefit)	4.255 kg CO ₂ e / kg

Disposal, reuse, recycling

Recycling of site residue	See SDS (section 13)
Recycling of dismantled building material	Can be reworked
	See Environmental Product Declaration (EPD)
Recycling of packaging material	Can be reused or recycled
	See https://www.stocretec.de/s/service-tools/entsorgung
Circular economy at StoCretec	https://www.stocretec.de/s/nachhaltigkeit/kreislaufwirtschaft

Corporate responsibility at StoCretec

Guiding principles, management of the company	StoCretec's vision is to be the technology leader in the sustainable design of living space tailored to human needs. Worldwide. For further information please visit: www.stocretec.de
UN Global Compact - membership	StoCretec is a member of the UN Global Compact and is committed to upholding ten universally acknowledged principles taken from the areas of human rights, labour standards, environmental protection, and anti-corruption. For further information please visit: www.unglobalcompact.org

Supplier code of conduct	https://www.stocretec.de/cepcom/stocretec/Dokumente/nachhaltigkeit/Compliance/Sto-Supplier-Code-of-Conduct_01_12_23_DE.pdf
---------------------------------	---

Notes

Version	09
Creation and use	The information and data contained in this sustainability data sheet is based on our knowledge and experience. The publication of a new sustainability data sheet invalidates all previous versions. Please observe the information in the Technical Data Sheet and Safety Data Sheet. The latest version is available on the Internet. Formulations are subject to change!